

ZT-889-TU

Standalone/Network Fingerprint Time Attendance Machine



Personnel Device Attendance

Drag a column header here to gro

Select No.	Name
<input type="checkbox"/> 1	BIO1

Join to work Begin Date

Drag a column header here to

State	Id	Name
On job	1	MANZAN
On job	2	CORDE
On job	3	OLLET

Read records/All records : 125

Print Printer setup Scan Parameters User Group Close

Company Name Here General Log Report

Date	Time	Device	Serial No.	Department
11/15/2018 10:16:26 AM	1	1	MANZANO, ROLLY	
11/15/2018 10:35:31 AM	1	1	MANZANO, ROLLY	
11/15/2018 11:02:18 AM	1	1	MANZANO, ROLLY	
11/15/2018 11:28:37 AM	1	1	MANZANO, ROLLY	
11/15/2018 11:49:35 AM	1	1	MANZANO, ROLLY	
11/15/2018 11:49:38 AM	1	1	MANZANO, ROLLY	
11/15/2018 11:49:38 AM	1	1	MANZANO, ROLLY	
11/15/2018 12:05:34 PM	1	1	MANZANO, ROLLY	
11/15/2018 5:30:03 PM	1	1	MANZANO, ROLLY	
11/17/2018 2:06:46 AM	1	1	MANZANO, ROLLY	
11/15/2018 8:57:34 AM	1	1	MANZANO, ROLLY	
11/15/2018 1:49:07 PM	1	1	MANZANO, ROLLY	
11/15/2018 2:04:26 PM	1	1	MANZANO, ROLLY	
11/15/2018 2:04:27 PM	1	1	MANZANO, ROLLY	
11/15/2018 2:04:30 PM	1	1	MANZANO, ROLLY	
11/15/2018 2:04:32 PM	1	1	MANZANO, ROLLY	
11/15/2018 2:04:34 PM	1	1	MANZANO, ROLLY	
11/15/2018 2:09:08 PM	3	3	OLLET, ROSETTE	
11/15/2018 2:14:24 PM	1	1	MANZANO, ROLLY	
11/15/2018 10:48:37 AM	1	1	MANZANO, ROLLY	
11/20/2018 8:03:07 AM	1	1	MANZANO, ROLLY	

Total: 3

Professional A&T

2.8 inches Color Screen Touch Keypad USB link USB Disk TA Report output (Free SW) TCP/IP

Page 1 of 1

ZT889-TU DATASHEET

Elegant design, Big capacity FLASH and Open SDK, professional technical support, easy to integrate with various systems

Item	Specification
Working Mode	Offline (Standalone) or network (with software)
Matching Mode	1: N (recommend); 1:1
Power	Terminal input:12V @2A Wall adapter input: 100-240V, 50-60Hz
Fingerprint /Password Capacity	3000 fingerprint templates/3000 passwords default , could be extended to large capacity like 10000 by additional charge
RF ID card capacity	3000 (Optional)
Record Capacity	80000 records
Response Time	≤ 0.7s (full of 3000)
CPU	NUC972 Arm 9
FAR (False Acceptance Rate)	Less than 0.0001%
FRR (False Rejection Rate)	Less than 0.01%
Sensor Mode	Uncoated Optical Sensor, Scratch and impact resistant
Fingerprint Collector	1.8*1.8mm 500dpi optical sensor
Allowable Finger Rotation	±180
Recognition Mode	Fingerprint or PIN or ID card (Optional) or any combination
LCD Language	Chinese, English, Spanish, Turkish, Arabian, Japanese, Korean and other languages (Voice prompt supports Chinese and English and others need to be customized)
LCD Dimension	240*320 Dots 2.8 inch Color LCD
Keypad Legend	26 key (0-9,OK, ESC, MENU, On/off,←,↑,→,↓), function key F1-F8
Dimension	199(L) x 134(W) x 30(D) mm
Individual Box Size	300(L) x 206(W) x 54(D) mm
Net Weight	0.36 kg for single unit
Communication	TCP/IP, USB (USB Client), USB-Disk (USB-Host) , Via TCP/IP, USB-disk, it can send enrollment/fingerprint data to other ZT889 and free powerful management software is provided
Built-in timing bell out	Available
With software or not	Free software
Whole package includes	Device *1, Underlay *1,installation back panel *1, installation screw bag *1, power supply*1
Operating Temperature	0C- 40C
Operating Humidity	20%-80%

Note: The product is updated constantly and all the product parameters shown above are subject to change without notice.